

WARNING! RISK OF ELECTRIC SHOCK

All electrical connections must be in accordance with local codes, ordinances, or national codes. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified electrician.

Before starting installation, disconnect the power by turning off the circuit breaker or removing the fuse at fuse block. Turning power off using fan switch (speed control on/off) is not sufficient to prevent electrical shock.

NOTE: The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care are factors which cannot be built into any product. These factors must be supplied by the person (s) caring for and operating the unit.

1. Remove the switch housing cover from the switch housing. Remove and discard the center plug from the switch housing cover. Attach the light kit to the switch housing cover by feeding the light kit wires (black and white) through the hole of switch housing cover and then screw it onto the switch housing by nut & lock washer. Be sure it is tight enough to prevent light kit from vibrating loose. (Fig. 1)
2. While holding the light kit under your fan, Locate two single white and blue wires in the switch housing labeled FOR LIGHT, make the polarized plug connections:
 - White to white
 - Blue to black
3. Carefully push all wires back into the switch housing, then install the light kit assembly onto the switch housing with 3 screws provided. Be sure to tighten all screws. (Fig. 1)
4. Pass the two pull chains on the switch housing through the chain holders located on the light kit, Install the fobs to the pull chains. (Fig. 2)
5. Install 1 x 9 Watt LED bulb (included). (Fig. 2)
6. Place the glass shade to the light kit with the thumb screws provided. (Fig. 2)

