

WARNING! RISK OF ELECTRIC SHOCK

All electrical connections must be in accordance with local codes, ordinances, or national codes. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified electrician.

Before starting installation, disconnect the power by turning off the circuit breaker or removing the fuse at fuse block. Turning power off using fan switch (speed control on/off) is not sufficient to prevent electrical shock.

NOTE: The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care are factors which cannot be built into any product. These factors must be supplied by the person (s) caring for and operating the unit.

1. Remove the detachable switch housing from the control cup plate. (Figure 1)
2. Remove and discard the center plug from the switch housing. Attach the light kit to the switch housing by feeding the light kit wires (black and white) through the hole of switch housing and then screw it onto the switch housing by nut & lock washer. Be sure it is tight enough to prevent light kit from vibrating loose. (Fig. 2)
3. Make polarized wire connection for 2 light kit wires to 2 wires from the switch housing, connect white to white and black to blue wires. (Figure 2)
4. While holding the light kit assembly under your fan, snap together the cannon plugs .
5. Carefully push all wires back into the switch housing, then install the light kit assembly onto the control cup plate with 3 screws provided. Be sure to tighten all screws. (Fig. 3)
6. Install 2 x 9 Watt LED bulbs (included). (Figure 3)
7. Place the glass shade over the light kit and secure it with the decorative nut provided. DO NOT OVER TIGHTEN. (Figure 3)
8. Pass the two pull chains on the switch housing and the light kit through the chain holders located on the light fitter, install the acrylic knobs to the pull chains. (Figure 3)

