

## ASSEMBLY AND INSTALLATION INSTRUCTIONS

**WARNING:** TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

### Installation Steps:

1. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to lose any small parts necessary for installation.
2. Attach the universal crossbar to the outlet box by using two outlet box screws upwards.
3. Guide the supply wires and ground wire from outlet box through the center hole on the universal crossbar.
4. Make wire connections:
  - attach fixture ground wire to supply ground wire using a wire nut or attach them to the universal crossbar with a green ground screw.
  - attach white wire from light to white wire from power source with a wire nut.
  - attach black wire from light to black wire from power source with a wire nut.Observing: ground wire with ground wire, neutral wire with neutral wire, hot wire with hot wire.  
\*\*\*Make sure all wire connectors are secured and do not easily pull off with the slight tug.
5. Once all wires are connected, tuck them carefully into outlet box.
6. Place the canopy over universal crossbar and secure canopy to universal crossbar with mounting screws.
7. Assemble the glass shade and socket ring onto the socket, then secure the glass on socket tightly by threading the socket ring with socket wrench.
8. Install bulbs.(not included) (Please do not exceed the maximum capacity which is recommended on the fixture.)
9. Turn on the power at fuse or circuit box.

