

ASSEMBLY AND INSTALLATION INSTRUCTIONS

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF
WARNING: POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

1. Carefully unpack and lay all parts on a clean, level surface.
2. Determine the desired length of stems needed for installation. Use any combination of the three tubes (G, H & I) to achieve the desired length. Use nipples provided to connect stems.
3. Feed the fixture wires from the coupler (K) through the tubes (G, I, J) and the swivel (F). Screw the components together until they are secured and do not come loose.
4. Pull the power supply wire out from the outlet box, and mount the mounting plate (A) to the outlet box using the outer box screws (C).
5. Attach the power supply wire to the fixture wire by connecting black supply wire to black (or smooth) fixture wire, and white supply wire to white (or ribbed) fixture wire, fixture ground wire to the power supply ground wire using wire nuts respectively.
6. Place the canopy (D) on the fixture by locking the swivel (F) tight. Adjust the fixture mounting screws (B) until they protrude out from the canopy (D), and secure into place using the decorative nuts (E) provided.
7. Secure the glass shade (M) to the nipple (L) by tightening the socket ring (N).
8. Install bulbs. (Please do not exceed the maximum capacity which is recommended on the fixture.)
9. Turn power on at fuse or circuit box.

