ASSEMBLY AND INSTALLATION INSTRUCTIONS

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF WARNING: POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

Installation Steps.

- 1. Carefully unpack and lay all parts on a clean, level surface.
- 2.Place the mounting plate(A) on the outlet box and mark the wall according to the location of the mounting hole. Then place four plastic anchors on the wall.
- 3. Attach the mounting plate(A) to the out let box using two outlet box screws(B). Then use a 4pcs tapping screw to run it through a mounting plate(A) mounting hole and lock it onto a plastic anchor.
- 4. Make wire connections:
 - --Attach the ground wire to house ground wire using a wire nut.
 - (Or attach them to the mounting plate (A) with a green ground screw.
 - --Attach white wire from light to white wire from power source with a wire nut.
 - --Attach black wire from light to black wire from power source with a wire nut.
- 5. Attach the back plate (C) to mounting plate (A) by using a mounting screw (D).
- 6.Install bulbs. (Please do not exceed the maximum capacity which is recommended on the fixture.)
- 7. Insert one end of glass shade (G) into cap (F) then then fasten cap (H) onto the other end of glass shade (G).
- 8. Secure the glass shade (G) to the caps by tightening the bushing (I).
- 9. Turn power on at fuse or circuit box.

