ASSEMBLY AND INSTALLATION INSTRUCTION

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

1. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to loose any small parts necessary for installation.

2. Fix the mounting plate to outlet box by using two outlet box screws.

3. Install bulb/bulbs.(not included) (Please do not exceed the maximum capacity which is recommended on the fixture.)

4. Insert the glass shade to lamp body and use knob nuts to secure glass as well as plastic washer onto lamp body.

5. Make wire connections:
   --attach ground wire to house ground wire using a wire nut or attach them to the mounting plate with a green ground screw.
   --attach white wire from light to white wire from power source with a wire nut.
   --attach black wire from light to black wire from power source with a wire nut.
   Observing: ground wire with ground wire, neutral wire with neutral wire, hot wire with hot wire.
   ***Make sure all wire connectors are secured and do not easily pull off with the slight tug.

6. Once all wires are connected, tuck them carefully into outlet box.

7. Place the backplate over the mounting plate and secure backplate to mounting plate with two mounting screws.

8. Turn on the power at the fuse or circuit box.

5277-1-xx, 5277-2-xx