

# ASSEMBLY AND INSTALLATION INSTRUCTIONS

## WARNING:

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

1. Thread 2 mounting screws properly into the relevant mounting holes pre-drilled on the cross bar.
2. Attach the cross bar to the outlet box using 2 outlet box screws upwards.
3. Make wire connections :
  - Attach ground wire to house ground wire using a wire nut or attach them to the cross bar with a green ground screw.
  - Attach white wire from light to white wire from power source with a wire nut.
  - Attach black wire from light to black wire from power source with a wire nut.

Observing: positive wire with positive wire, negative wire with negative wire, ground wire with ground wire.
4. Tuck the wire connections neatly into the outlet box.
5. Attach the fixture body to the ceiling and let the 2 mounting screws pass through the 2 pre-drilled holes on the canopy and fix it in place by ball nuts.
6. Install bulb. (not included) (Please do not exceed the maximum capacity which is recommended on the fixture.)
7. Tuck the wire connections neatly into the outlet box.
8. Attach the canopy to the ceiling, and secure it with ball nut .
9. Put the glass shade onto the socket and secure it by the cap.
10. Place socket through the opening on the outer ring
11. Install bulb.(not included) (Please do not exceed the maximum capacity which is recommended on the fixture.)
12. Align the hole on the glass with the hole on socket, secure with ball nut.
13. Turn on the power at fuse or circuit box.

