

ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

Installation Steps:

1. Carefully unpack your new fixture and lay out all the parts on clear area. Take care not to lose any small parts necessary for installation.
2. Fasten the all thread pipe and tube into the hex coupling on lamp body. Attach the cover onto the top of tube, lock it securely with the fixture loop.
3. Assemble the threaded nipple onto the cross bar and lock it in place by hex nut. Attach the cross bar assembly to outlet box by using two outlet box screws upwards.
4. Determine the length of chain needed, using pliers to disconnect the unneeded chain. Connect desired chain length using chain links. Put one chain link on the fixture loop and the other one on screw collar.
5. Weave the fixture wires including ground wire through fixture loop, every other chain, screw collar, collar ring, canopy, and threaded nipple on the cross bar. Secure the screw collar onto the threaded nipple.
6. Make wire connections:
 - Attach ground wire to house ground wire using a wire nut or attach them to the cross bar with a green ground screw.
 - Attach white or ribbed wire(neutral) from light to white wire from power source with a wire nut.
 - Attach black or smooth wire(hot) from light to black wire from power source with a wire nut.Observing: ground wire with ground wire, neutral wire with neutral wire, hot wire with hot wire.
***Make sure all wire connectors are secured and do not easily pull off with the slight tug.
7. Tuck the wire connections neatly into the outlet box.
8. Attach the canopy to the ceiling then thread the collar ring on screw collar to secure the canopy.
9. Assemble the glass shade and socket ring onto the socket, then secure the glass on socket tightly by threading the socket ring with socket wrench.
10. Install bulbs. (not included) (Please do not exceed the maximum capacity which is recommended on the fixture.)
11. Turn on the power at the fuse or circuit box.

