

ASSEMBLY AND INSTALLATION INSTRUCTIONS

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF
WARNING: POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

1. Carefully unpack and lay all parts on a clean, level surface.
2. Please follow the letters on the schematic diagram separate the arms (L) to ensure there is an equal space between them .
3. Determine the desired length from the intended ceiling or mounting surface. Using the combination of three tube (G, I, J) lengths to give your desired length and screw them together using the nipples (H) provided on each end of the assembled tubes (G, I, J).
4. Feed the fixture wires from the coupler (K) through the tubes (G, I, J) and the canopy (D). Screw the components together until they are secured and do not come loose.
5. Pull the power supply wire out from the outlet box, and mount the mounting plate (A) to the outlet box using the outer box screws (C).
6. Make wire connections:
 - Attach ground wire to house ground wire using a wire nut. (Or attach them to the cross bar with a green ground screw).
 - Attach white wire from light to white wire from power source with a wire nut.
 - Attach black wire from light to black wire from power source with a wire nut.
7. Tuck the wire connections neatly into the outlet box.
8. Place the canopy (D) on the fixture by locking the swivel (F) tight. Adjust the fixture mounting screws (B) until they protrude out from the canopy (D), and secure into place using the decorative nuts (E) provided.
9. Install bulbs. (Please do not exceed the maximum capacity which is recommended on the fixture.)
10. Turn power on at fuse or circuit box.

