


ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK , BE SURE TO SHUT OFF POWER WHILE INSTALLING OR SERVICING THIS FIXTURE .

NOTE : Before installing ,consult local electrical codes for wiring and grounding requirement

1. Thread the Tube (D) onto the nipple (C),
Then thread fixture loop (B) onto the nipple tightly.
2. Assemble the Nipple (A)
onto the Cross bar , and lock it
in place by Hex nut (A).
3. Attach the Cross bar to outlet
box using 2 outlet box screws upwards.
4. Determine the length of the
Chain you need .using pliers to
disconnect the extra chain .and
discard it away;
5. Weave fixture wires and ground
wire through the every other chain
links. Fixture loop , canopy (D). and
hang the chain to the fixture loop .
6. Make wire connections :
 --- Attach ground wire to house
ground wire using a wire nut (or
attach them to the cross bar with a
green ground screw).
 --- Attach ribbed wire from light to
white wire from power source with a wire nut .
 --- Attach smooth wire from light to
black wire from power source with a
wire nut .
7. Tuck the wire connections neatly into
the Outlet box ;
8. Attach the canopy (I) to the ceiling ,
and let the nipple (A) protrude
through the pre-drilled hole on the
canopy (I) , and secure with finial (H) .
9. Turn power on at fuse or circuit box.



66-8-6980