

# ASSEMBLY AND INSTALLATION INSTRUCTIONS

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF  
**WARNING:** POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

**NOTE:** Before installing, consult local electrical codes for wiring and grounding requirement.

1. Carefully unpack and lay all parts on a clean, level surface.
2. Separate the arms (J) to ensure there is an equal space between them.
3. Determine the desired length from the intended ceiling or mounting surface. Using the combination of three tube (F, G, H) lengths to give your desired length and screw them together using the 4pcs mounting screws(E) provided on each end of the assembled tubes (F, G, H).
4. Feed the fixture wires from the fixture body(I) through the tubes (F, G, H) and the canopy (D). Screw the components together until they are secured and do not come loose.
5. Attach the mounting plate(A) to outlet box using two outlet box screws(C) upwards.
6. Make wire connections:
  - Attach ground wire to house ground wire using a wire nut. (Or attach them to the cross bar with a green ground screw).
  - Attach white wire from light to white wire from power source with a wire nut.
  - Attach black wire from light to black wire from power source with a wire nut.
7. Tuck the wire connections neatly into the outlet box.
8. Fix the canopy (D) on the support mounting plate (A) with mounting Screws (B), as shown in the figure.
9. Secure the shade (L) to the socket (K) by tightening the socket ring (M).
10. Install bulbs. (Please do not exceed the maximum capacity which is recommended on the fixture.)
11. Turn power on at fuse or circuit box.

