

# ASSEMBLY AND INSTALLATION INSTRUCTIONS

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF  
**WARNING:** POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

**NOTE:** Before installing, consult local electrical codes for wiring and grounding requirement.

1. Carefully unpack and lay all parts on a clean, level surface.
2. Determine mounting plate (A) use a pencil to mark the location on the wall for the Plastic Anchors. Make a hole slightly smaller than the diameter of the Plastic Anchors. Insert the Plastic Anchors and tap it into the hole in the ceiling until secure. Attach the mounting plate (A) to Plastic anchor by using three Tapping Screws.
3. Pull the power supply wire out from the outlet box, and mount the mounting plate (A) to the outlet box using the outer box screws (C).
4. Determine the desired length from the intended ceiling or mounting surface. Use a screwdriver to loosen the plastic screws (H) adjust the wire (the maximum size of the wire installation is 10 feet by adjusting the wire to offset each pendant up and down)
5. Tighten plastic screws (H) onto fixed nut (I) and then adjust knot (J) to secure cord.
6. Attach the power supply wire to the fixture wire by connecting black supply wire to black (or smooth) fixture wire, and white supply wire to white (or ribbed) fixture wire, fixture ground wire to the power supply ground wire using wire nuts respectively.
7. Attach canopy (D) to mounting plate (A) with three mounting screws (B).
8. Install bulbs. (Please do not exceed the maximum capacity which is recommended on the fixture.)
9. Attach glass shade (G) to cap (F) with three decorative screw (E).
10. Turn power on at fuse or circuit box.

