


ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING:

TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF
POWER WHILE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirement.

1. Determine the length of stem/stems you need.
2. Thread one stem onto the nipple and thread stem nipple onto top of the stem.
3. Feed fixture wires and ground wire through the stem and stem nipple.
4. Repeat step 2 and step 3 until all desired stems are connected.
5. Thread the swivel into top of the stems tightly.
6. Weave fixture wires and ground wire through the swivel and canopy.
7. Attach the cross bar to the outlet box using 2 outlet box screws upward.
8. Make wire connections with wire nuts:
 - Attach ground wire to house ground wire using a wire nut or attach them to the cross bar with a green ground screw.
 - Attach white wire from light to white wire from power source with a wire nut.
 - Attach black wire from light to black wire from power source with a wire nut.
9. Tuck the wire connections neatly into the outlet box.
10. Attach the canopy to the ceiling and let the two canopy screws protrude through the two pre-drilled holes on the canopy and secure it with canopy screw.
11. Secure finial B to the socket cup. Put the glass shade onto the socket and use the outer ring to fix it, then put metal ring B onto metal ring A and secure them by finial A.
12. Install bulb.(not included) (Please do not exceed the maximum capacity which is recommended on the fixture.)
13. Turn on the power at fuse or circuit box.



886-65
886-80
886-86
886-92
886-8086